

FLOWLOCK RC 325

RAPID CURE REPAIR MORTAR FOR CONCRETE FLOORS AND ROADS

Flowlock RC 325 is a high strength, rapid-cure repair mortar for areas exposed to heavy wheel traffic, such as roads, industrial floors, loading areas and bridges. The unique formulation with fibre reinforcements gives high mechanical strength and high resistance to impacts.

Full cure takes only 2 hours, allowing areas to quickly return to full use.

USES

- Urgent repairs of concrete floors and surfacing – 2-hour cure time
- Applications bearing heavy wheel traffic and use, for example: roads, industrial floors, loading areas and bridges.
- Concrete floor repair and refurbishment prior to application of a Flowlock Floor Coating System
- Minimum thickness 3mm
- Maximum thickness 100mm

BENEFITS

- Full cure takes only 2 hours, allowing areas to quickly return to full use.
- High mechanical strength and high resistance to impacts.
- Single component product is very easy to use.
- Very good adhesion to concrete.
- Can be applied to damp surfaces.
- Chloride free

COVERAGE

Estimated coverage is 15 litres volume per 25 kg container.

FLOWLOCK
(division of Rooflock)

T: 0161 945 1440 **E:** info@flowlock.co.uk **W:** www.flowlock.co.uk
A: Catford Road, Roundthorn Industrial Estate, Manchester, M23 9LR